

DULUX ALUMINIUM WOOD PRIMER

61

PRODUCT INFORMATION

Typical Use	<p>Dulux Aluminium Wood Primer is a solvent-based primer suitable for use on all types of soft and hard woods, inside and outside, especially those which are highly resinous.</p> <p>It can also be used as a sealer for aged creosoted or bitumen coated surfaces or as a first coat for Dulux Aluminium Paint, where a two coat aluminium system is required.</p> <p>Complies with BS 4756</p> <p>Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.</p>
Pack Size	1, 2.5 and 5 litre.
Colour Range	Silver.
Film Properties	
Composition (nominal)	<p>Pigment: Non-leafing Aluminium.</p> <p>Binder: Alkyd Resin.</p> <p>Solvent: White Spirit.</p>
Volume Solids	37% (nominal).
Mixing Ratio	
Thinning	Thinning is not required.
Application Method	<p>Brush only.</p> <p>For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.</p>
Pot Life	
Film Thickness	
Drying Times	Single coat at standard thickness:
Handle	
Theoretical Coverage	18m ² / litre at 20 microns DFT
Spray Recommendations	
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 17m ² / litre.
Cleaning Up	<p>After use, remove as much paint as possible from brushes before cleaning with Dulux Thinner Number 41 or white spirit.</p> <p>Do not use or store in extremes of temperature.</p>

SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

Avoid the inhalation of dust.
Wear a suitable face mask if dry sanding.
Any surface defects must be filled with a suitable filler.

SYSTEM INFORMATION

Stir thoroughly before use.

After suitable surface preparation, apply 1 or 2 coats of **Dulux** Aluminum Wood Primer.
Where the wood is highly resinous wood or as a sealer over aged creosote or bitumen coated surfaces, apply 2 coats of **Dulux** Aluminum Wood Primer, allowing 24 hours between coats.
Finish with an appropriate **Dulux** paint system.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (read this section before use)

SOLVENT-BASED PAINT PRODUCT UN 1263 CLASS 3

FLAMMABLE.

Repeat exposure may cause skin dryness and cracking.

Caution, pressure may build up in the container.

Remove lid with care.

When removing lid and applying paint it is advisable to wear suitable eye protection.

Keep away from sources of ignition.

No smoking.

Contains white spirit.

Use only in well ventilated areas.

Inside always keep doors and windows fully open during application and drying.

When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.

Avoid contact with skin and eyes.

When painting it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from skin: use soap and water or a recognised skin cleaner.

Keep out of reach of children.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

This product contains no added lead.

However, the wood and metal surfaces of the building, especially if it is pre-1960, may have been decorated in the past with a paint made with lead pigments.

Preparation and removal of such paint can be hazardous.

For full health and safety information see safety data sheet.

For further information or if you have any concern about using this product contact:

Dulux Paints Ireland Ltd.

Shandon Works, Commons Road, PO Box 45, Cork.

Tel: (021) 4302381 Fax: (021) 4302563

Davitt Road, Crumlin, Dublin 12

Tel: (01) 4556099 Fax: (01) 4558578

Website: www.dulux.ie

VOC Content High 25% - 50%.

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux is a Trademark of ICI.

© ICI 00

Approximate Weight 6 kg



Lift with Care

5 LITRE OF PAINT
+CONTAINER