



# GLIDDEN PRIMECOAT ACRYLIC WOOD PRIMER UNDERCOAT

## G101

### PRODUCT INFORMATION

<b>Typical Use</b>	Glidden Primecoat Acrylic Wood Primer Undercoat is a high opacity, dual purpose product which is fast drying and has excellent adhesion. Suitable for both interior and exterior use. Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.	
<b>Pack Size</b>	1, 2.5, and 5 litres.	
<b>Colour Range</b>	White only.	
<b>Composition (nominal)</b>	<b>Pigment:</b>	Non Lead Pigments.
	<b>Binder:</b>	Acrylic Copolymer.
	<b>Solvent:</b>	Water.
<b>Volume Solids</b>	35% (nominal).	
<b>Application Method</b>	Brush, roller or spray.	
<b>Drying Times</b>	<i>Single coat at standard thickness:</i>	
	<b>Touch Dry:</b>	Dependent upon temperature and humidity at the time of painting.
	<b>Recoat:</b>	2 hours.
<b>Practical Coverage</b>	Up to 12m <sup>2</sup> per litre on smooth surfaces of average porosity.	
<b>Thinning</b>	<b>Sealing new or bare surfaces:</b>	Add up to 1 part clean water to 5 parts paint.
	<b>Normal use (not to be exceeded):</b>	Add up to 1 part clean water to 10 parts paint.
	<b>Conventional spray application:</b>	Add up to 1 part clean water to 2.5 parts paint.
	<b>Airless spray application:</b>	Add up to 1 part clean water to 5 parts paint.
<b>Spray Recommendations</b>	<b>Conventional Spray:</b>	Satisfactory through most types of conventional spray equipment.
	<b>Airless Spray:</b>	A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.43mm (17 thou) and a spray tip angle 60°.
<b>Cleaning Up</b>	After use, remove as much paint as possible from brushes before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.	

### SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Treat any knots in wood with **Dulux Trade** Knotting Solution.

Any surface defects must be filled with a suitable filler.

Issued January 2003

# GLIDDEN PRIMECOAT ACRYLIC WOOD PRIMER UNDERCOAT

# G101

## SYSTEM INFORMATION

Stir thoroughly before use.

**New or bare surfaces:**

2 coats of Glidden Primecoat Acrylic Wood Primer Undercoat.

**Previously painted surfaces:**

1 coat of Glidden Primecoat Acrylic Wood Primer Undercoat.

Allow to dry for a minimum of 2 hours between coats, then apply an appropriate Glidden Trade paint system.

## SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

### WATER-BASED PAINT

Ensure good ventilation during application and drying.

Do not breathe spray. When applying by spray inside, wearing a cartridge mask of Assigned Protection Factor 40 x OEL for particulates is recommended. This should be confirmed by your COSHH assessment. Contact your merchant about masks.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleaner. Do not use solvent, thinners or white spirit.

Keep out of the reach of children. Do not use or store by hanging on a hook. Do not empty into drains or watercourses. Some local authorities have special facilities for disposing of waste paint.

Safety data sheet available for professional user on request.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

This product contains no added lead. However, the wood and metal surfaces of the building, especially if it is pre-1960, may have been decorated in the past with a paint made with lead pigments. Preparation and removal of such paint can be hazardous. For a free leaflet explaining how the surface should be prepared safely contact:

ICI Paints Technical Group, at:  
ICI Paints, Wexham Road, Slough  
SL2 5DS.

Tel: 0870 242 1100

See [www.duluxtrade.co.uk](http://www.duluxtrade.co.uk)

**VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.**

The ICI Roundel, **Dulux Trade** and the Glidden Oval are trade marks of the ICI Group.

© ICI (04/02/03 IT)

