



20 Oct 2000

Glidden Ultrahide Soft Sheen

75

PRODUCT INFORMATION

Typical Use	Glidden Ultrahide Soft Sheen is a low sheen emulsion that resists scuffing, staining and abrasion. Suitable for interior wall and ceiling surfaces. Particularly suited for large job applications in commercial, institutional and industrial structures. Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.
Pack Size	10 litre.
Colour Range	White and Magnolia
Film Properties	Chemical Resistance: Not suitable. Heat Resistance: Not suitable for use on heated surfaces eg radiators. Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments.
Composition (nominal)	Pigment: Lightfast Non-Lead Pigments. Binder: PVA Copolymer. Solvent: Water.
Volume Solids	40% (nominal).
Mixing Ratio	
Thinning	Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint. Normal use: For normal use thinning should not exceed 1 part water to 10 parts paint. Conventional spray application: Add up to 1 part clean water to 4 parts paint. Airless spray application: Thinning is not required.
Application Method	Brush roller or spray.
Pot Life	
Film Thickness	
Drying Times	<i>Single coat at standard thickness:</i>
Handle	
Theoretical Coverage	16m ² / litre at 25 microns DFT
Spray Recommendations	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 14m ² / litre.
Cleaning Up	After use, remove as much paint as possible from equipment before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease

and salts.

New plaster and masonry must be fully dry before priming.

Avoid the inhalation of dust.

Wear a suitable face mask if dry sanding.

SYSTEM INFORMATION

Stir thoroughly before use.

On very absorbent surfaces apply a sealing coat of thinned Glidden Ultrahide Soft Sheen

Finishing: Apply 2 coats of Glidden Ultrahide High Opacity Vinyl Matt. On previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION (read this section before use)

WATER-BASED PAINT PRODUCT

Ensure good ventilation during application and drying.

Do not breathe spray.

When applying by spray inside or in confined spaces, the wearing of air-fed respiratory protective equipment will always be necessary.

Avoid contact with skin and eyes.

When painting it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from skin: use soap and water or a recognised skin cleaner.

Keep out of reach of children.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

This product contains no added lead.

However, the wood and metal surfaces of the building, especially if it is pre-1960, may have been decorated in the past with a paint made with lead pigments.

Preparation and removal of such paint can be hazardous.

For full health and safety information see safety data sheet.

For further information or if you have any concern about using this product contact:

Dulux Paints Ireland Ltd.

Shandon Works, Commons Road, PO Box 45, Cork.

Tel: (021) 4302381 Fax: (021) 4302563

Davitt Road, Crumlin, Dublin 12

Tel: (01) 4556099 Fax: (01) 4558578

Website: www.dulux.ie

VOC Content Low 0.30% - 7.99%.

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux is a Trademark of ICI.

© ICI 00



**5 LITRE OF PAINT
+CONTAINER**