



SDSPT132

POLYCELL TRADE – POLYFILLA EXPANDING GUN FOAM SAFETY DATA SHEET

Issued 04/2008

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT NUMBER : 876-6031

PRODUCT NAME : Polycell Trade – Polyfilla Expanding Gun Foam

Supplied by :
ICI Paints,
Wexham Road,
Slough,
Berkshire,
SL2 5DS, U.K.

E-mail address : duluxtrade_advice@ici.com

Emergency Telephone : Slough +44 (0) 1753 550000

INTENDED USE

ICI Paints' products are intended for use in the process of decorating buildings surfaces. Refer to product label for specific usage details.

2. HAZARDS IDENTIFICATION

This product has been assessed under the CHIP Regulations and is classified as follows:

Indication(s) of Danger

Extremely Flammable, Harmful

Symbol Letter(s)

F+,Xn

Category(ies) of Danger

Extremely Flammable, Irritant, Sensitising (Inhalation)

Warning Label Phrases

R12 Extremely flammable.

R42/43 May cause sensitisation by inhalation and skin contact.

R36/37/38 Irritating to eyes, respiratory system and skin.

- P91 Contains isocyanates. See information supplied by the manufacturer.
- P96 Pressurised container: protect from sunlight and do not expose to temperature exceeding 50 degrees C. Do not pierce or burn, even after use.
- P97 Do not spray on a naked flame or any incandescant material. Keep away from sources of ignition
- No smoking. Keep out of the reach of children.

Information on Occupational Exposure Limits is given in Section 8.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a physico-chemical, health or environmental hazard within the meaning of the CHIP Regulations or which are assigned occupational exposure limits.

EC No.	CAS No.	HAZARDOUS INGREDIENTS	%	CLASSIFICATION	
202-966-0	101-68-8	DIPHENYLMETHANE DIISOCYANATE	10-25	Xn	R20-36/37/38-42-43
200-857-2	75-28-5	ISOBUTANE	2.5-10	F+	R12
204-065-8	115-10-6	DIMETHYL ETHER	2.5-10	F+	R12
200-827-9	74-98-6	PROPANE	2.5-10	F+	R12

Note: The text for R phrase codes shown above (if any) is given in section 16.

Note: 'EC Number' if quoted is the EINECS or ELINCS number.

4. FIRST-AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped administer artificial respiration. Give nothing by mouth. If unconscious place in the recovery position. Seek medical advice.

EYE CONTACT: Remove contact lenses. Irrigate copiously with clean, fresh water for at least 10 minutes, holding lids apart. Seek medical advice.

SKIN CONTACT: Remove contaminated clothing, wash skin thoroughly with soap and water, or use a proprietary skin cleanser. Do not use solvents or thinners. Seek medical advice if symptoms persist.

INGESTION: If accidentally swallowed, DO NOT INDUCE VOMITING. Keep at rest and obtain medical attention.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Recommended - alcohol resistant foam, CO2, powders.

Not to be used - waterjet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Fire fighters should wear self-contained breathing apparatus.

Closed containers exposed to fire should be cooled with water. Do not allow run-off from fire-fighting to enter drains or water-courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude non-essential personnel.

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in section 8. Contain and collect spillage with non-combustible absorbent materials, eg sand, earth, vermiculite or diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

7. HANDLING AND STORAGE

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used. Persons using this product should be subject to appropriate health surveillance.

HANDLING CONDITIONS: Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected by the appropriate standard. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of vapour and mist. Smoking, eating and drinking should be prohibited in storage and use areas. For personal protective equipment see Section 8. Always keep in containers made of the same material as the supply container, or in containers that are compatible with the product. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

Preparations may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing, and floors should be of the conducting type.

Keep container tightly closed. Precautions should be taken to minimise exposure to atmospheric humidity or water : Carbon Dioxide will be formed, which in closed containers can result in pressurisation. Care should be taken when re-opening partly used containers.

STORAGE CONDITIONS: Observe the label precautions. Store in a cool, dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not use or store any paint container by hanging on a hook.

The Manual Handling Operations Regulations 1993 may apply to the handling of certain Paint Products. Products packed in containers of 5 litres and above will be marked with a guide weight; refer to these weights when carrying out an assessment.

The principles contained in the HSE guidance note Storage of Packaged Dangerous Substances, should be observed when storing this product. Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water.

SPECIFIC USE(s): Where applicable refer to the product label and literature for the application and use instructions. This product must not be spray applied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

HAZARDOUS INGREDIENT	LTEL (8hr TWA) ppm	LTEL (8hr TWA) mg/m ³	STEL (15 mins) ppm	STEL (15 mins) mg/m ³	Notes
DIPHENYLMETHANE DIISOCYANATE		0.02		0.07	WEL,Sen
DIMETHYL ETHER	400	750	500	940	WEL
PROPANE	500	900			

OEL - Occupational Exposure Limits

WEL - Workplace Exposure Limit

SUP - Manufacturer's recommended Limit

LTEL - Long-term Exposure Limit.

TWA - Time weighted Average

STEL - Short term Exposure Limit (15mins)
sk - Risk of absorption through unbroken skin
sen - Respiratory sensitiser
rd - Figure quoted is for Respirable dust
id - Figure quoted is for Inhalable dust

Further guidance on WELs and OELs, and on occupational exposure to harmful materials (including mixed exposures) is given in HSE Guidance Note EH40.

EXPOSURE CONTROLS

Before commencing work, ensure that a COSHH Assessment has been carried out. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of local regulations.

RESPIRATORY PROTECTION: Avoid the inhalation of vapour, particulates and spray mist. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general ventilation. If this is not sufficient to maintain concentrations of particulates and solvent vapour below the occupational exposure limit, respiratory protection must be worn.

The selection of respiratory equipment should be in accordance with BS 4275. Recommendations for the selection, use and maintenance of Respiratory Equipment, and the current certificates of approval are issued annually by the Health and Safety Executive.

When isocyanate-based paints are spray-applied, the aerosol mist droplets produced are mainly of respirable size and inhalation must therefore be avoided. Air-fed respiratory equipment must be worn even when good ventilation is provided. Steps must be taken to ensure that persons nearby who may be unconnected with the spraying operation are not affected.

HAND PROTECTION: Wear suitable gloves for protection against materials in section 3.

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed.

EYE PROTECTION: Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION: Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

FLATTING: Protective gloves should be worn to avoid the risk of skin irritation. When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet flattening or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry flattening cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the occupational hygiene (COSHH) assessment, taking into account the occupational hygiene exposure standard for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

The Control of Lead at Work approved code of practice 1998 (ISBN 0 71 7615065) should be consulted for advice on protective clothing and personal hygiene precautions.

Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations.

All scrapings, dust, etc. should be disposed of by the professional painting contractor as Special (Hazardous) Waste, with the relevant documentation under The Special Waste Regulations 1996 plus amendment 2001, The Environmental Protection (Duty of Care) Regulations 1991, The Controlled Waste Registration of Carriers and Seizure of Vehicles Regulations 1991 plus amendment 1998 and the Controlled Waste Regulations 1992 plus amendment 1993.

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Extra precautions will need to be taken when burning off old lead based paints (See above - "Flattening" for relevance to work on older property, ie pre 1960) as fumes containing lead will be produced.

It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the occupational hygiene (COSHH) assessment, taking into account the occupational hygiene exposure standard for lead in air.

Similar precautions to those given above under the Flattening section should be taken with reference to protective clothing, disposal

of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

ENVIRONMENTAL EXPOSURE CONTROLS: See section 12 for detailed information.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State :	Aerosol	
Flash Point :	- 18 - < 21	°C
Specific Gravity :	0.960	
Water Miscibility :	No Information	Not miscible with water. Reacts with water, liberating carbon dioxide and forming an inert insoluble solid.
pH :	No Information	
Viscosity :	< 30	(ISO 6mm Range)
Initial Boiling Point in °C :	-25	
Explosion limits:	Lower - approx. 0.8% Upper - no information	

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Extremes of temperature.

To prevent the creation of flammable concentrations of vapour in air, good natural ventilation, and if necessary, local exhaust ventilation, should be provided. The accumulation of dry overspray, contaminated rags, etc may result in spontaneous combustion. Good housekeeping standards plus the regular and safe removal of waste materials will minimise the risk.

MATERIALS TO AVOID: Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.

The product reacts slowly with water resulting in evolution of Carbon Dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke and oxides of nitrogen.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. The product has been assessed following the conventional method in the CHIP Regulations and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See Sections 2 and 15 for details of the resulting hazard classification.

Over-exposures of vapour are irritating to eyes and respiratory system. Excessive concentrations may produce effects on the central nervous system including drowsiness. In extreme cases loss of consciousness may result. Long term exposure to vapour concentrations in excess of quoted OELs may result in adverse health effects. Splashes entering the eye will cause discomfort and possible damage. Prolonged contact with the skin may have a defatting effect which may lead to skin irritation and in some cases dermatitis.

Moisture-cured, two-pack and blocked isocyanate containing products may cause irritation and/or sensitisation to the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Persons with a history of chronic or recurrent respiratory disease or chronic eczema should not be employed in any process in which these products are used. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

COSHH requires that persons exposed to products containing isocyanates, which are respiratory sensitisers, are subject to appropriate health surveillance. Publications giving guidance on health surveillance are listed in section 16. Employees should be provided with a copy of the HSE pocket card containing information on isocyanate two pack paints.

12. ECOLOGICAL INFORMATION

There is no specific data available on the product itself.

The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Products classified as Marine Pollutants are indicated as such under Transport (section 14).

Products classified as Dangerous For the Environment are indicated as such in sections 2 and 15.

Any substances in the product that are classified as Dangerous for the Environment, present at concentrations above those requiring listing are given in section 3.

13. DISPOSAL CONSIDERATIONS

Wastes, including emptied containers, should be disposed of in accordance with national regulations.

CODES ACCORDING TO THE LIST OF WASTES REGULATIONS:

Product as supplied: Assigned as hazardous waste code 16 05 04* Gases in pressure containers (including halons) containing dangerous substances.

Part-used containers, containing dried residues of the supplied product: Assigned as hazardous waste code 16 05 04* Gases in pressure containers (including halons) containing dangerous substances.

Used containers, rigorously scraped out and containing dried residues of the supplied product: Not Applicable.

"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.

These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.

14. TRANSPORT INFORMATION

Transport within user's premises:

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport to be in accordance with ADR for road, IMDG for sea. The transport classifications provided in this section are not valid for transport by Air. Please call the number in section 1 of this safety data sheet to obtain more information on this products classification for Air transport.

ADR Classification Information

UN Number : 1950
Proper Shipping Name : AEROSOLS
Hazard Class : 2
Sub-Hazard Class :
Packing Group : .
Technical Name (NOS only) :
Ltd Qty Code : LQ2
Packing Instructions : P204

IMDG Classification Information

UN Number : 1950
Proper Shipping Name : AEROSOLS
Hazard Class : 2
Sub-Hazard Class :
Packing Group :
Technical Name (NOS only) :
Ltd Qty Maximum : See SP277
Packing Instructions : P003
Marine Pollutant if indicated here:
Emergency Schedule No : F-D,S-U
Flashpoint : - 18 - < 21

15. REGULATORY INFORMATION

This product has been assessed under the CHIP Regulations and is classified as follows:

NAMED SUBSTANCES

Contains

DIPHENYLMETHANE DIISOCYANATE

INDICATION(S) OF DANGER

Extremely Flammable, Harmful

SYMBOLS LETTER(S)

F+,Xn

WARNING LABEL PHRASES:

J37(G) SOLVENT-BASED PRODUCT
R42/43 May cause sensitisation by inhalation and skin contact.
R36/37/38 Irritating to eyes, respiratory system and skin.

P91 Contains isocyanates. See information supplied by the manufacturer.
P96 Pressurised container: protect from sunlight and do not expose to temperature exceeding 50 degrees C. Do not pierce or burn, even after use.
P97 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – No

smoking. Keep out of the reach of children.
If working close to a boiler, naked flame or any other sources of sparks or ignition such as electrical appliances, turn off before application.

A6	Solvent abuse can kill instantly.
S51	Use only in well ventilated areas.
S23	Do not breathe vapour.
S24/25	Avoid contact with skin and eyes.
S37/39	Wear suitable gloves and eye/face protection. Suitable gloves are neoprene, butyl rubber, pvc and polyethylene.
S28	In case of contact with skin remove foam immediately with a clean dry cloth and clean affected area with vegetable oil or wash immediately with plenty of water. Do not attempt to abrade as this may damage skin. Allow remaining foam to come off naturally.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S56	Dispose of this material and its container at hazardous or special waste collection point.
J18	Before use refer to safety data sheet.
J110	This includes waste hazard categories.
J45(E)	For further advice contact: ICI Paints Technical Group at: ICI Paints, Wexham Road, Slough SL2 5DS. Tel: 0870 242 1100. See www.duluxtrade.co.uk
J65	The Polycell Logo is a trademark of ICI.

Where 'J' and/or 'P' phrases are denoted, these are ICI Paints or paint industry reference codes to additional phrases.

16. OTHER INFORMATION

Text for R Phrases shown in section 3 describing each ingredient:

R12	Extremely flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R42	May cause sensitisation by inhalation.
R43	May cause sensitisation by skin contact.

The information in this safety data sheet is required in pursuant to the CHIP Regulations.

Guidance on the use of Isocyanate based paints is given in HSE Guidance Notes MS8 "Isocyanates - Medical Surveillance" and EH16 "Isocyanates - Toxic Hazards and Precautions" in guidelines published by the Paintmakers Association "Paint Users Safety Precautions" and in the HSE card "Your Health and 2-pack Spray Paints".

You should satisfy yourself that your COSHH Assessment is in accordance with the COSHH Regulations and Approved Code of Practice. ICI does not accept any responsibility for your COSHH Assessment. Other Reference: The Control of Substances Hazardous to Health Regulations (COSHH).

The information on this sheet is not a specification: it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product nor where instructions and recommendations are not followed.

We will be pleased to answer any specific enquiries regarding the safe use, storage and handling of our product.

Contact: ICI PAINTS Technical Group, Wexham Road, Slough, Berks. SL2 5DS
Telephone: 0870 242 1100

ICI Paints in the UK is part of Imperial Chemical Industries Limited and a member of the ICI Paints World Group. Registered in England No. 218019.
Registered office: 20 Manchester Square, London, W1U 3AN.